

CP- VNC-V51ZR3-VMD**5 MP Full HD WDR Array Vandal Dome Camera - 30Mtr.****Main Features**

- 1/2.7" 5MP PS CMOS Image Sensor
- 5MP(2592 x 1944): Max. 25 fps
- Ultra 265,H.265, H.264, MJPEG Triple-stream Encoding
- WDR(120dB), Day/Night (ICR), 2D/3D-DNR,Corridor mode, ROI, Digital defog, AWB, AGC, BLC, HLC
- 2.7~13.5mm Motorized Lens
- Array Range of 30 Mtrs, Smart IR, IP67, IK10, PoE
- Supports Instastream technology, save disk space and bandwidth upto 70%
- Mobile Software: Android, iOS
- CMS Software: IVMS

**Instastream****CE FC** **RoHS**
COMPLIANT

CP- VNC-V51ZR3-VMD

5 MP Full HD WDR Array Vandal Dome Camera - 30Mtr.

Feature

Image Sensor
 Minimum Illumination
 Shutter Speed
 White Balance
 Lens
 Gain Control (AGC)
 Angle of View
 DORI Distance
 Video Compression
 Back Light Compensation
 S/N Ratio
 Video Streaming
 Video Output
 Resolution
 Frame Rate
 Motion detection
 Privacy Mask
 ICR
 ROI
 Audio Input
 Audio Output
 Audio Compression
 Audio
 Alarm IN
 Alarm Out
 Protocol
 Network Storage
 Dewarping

Specification

1/2.7" 5MP Progressive scan CMOS
 Colour: 0.002Lux (F1.2, AGC ON) 0Lux with IR
 Auto/Manual, shutter time: 1~1/100000 s
 Auto/Manual
 2.7~13.5mm Motorized Lens
 Auto/Manual
 93.38° ~ 28.56° (H), 88° ~ 16.4° (V), 121.4° ~ 33.7° (O)
 2.7mm– 60.8 Detect (m) , 24.3 Observe (m), 12.2 Recognize (m), 6.1 Identify (m)
 13.5mm– 303.8 Detect (m) , 121.5 Observe (m), 60.8 Recognize (m), 30.4 Identify (m)
 Ultra 265,H.265, H.264, MJPEG
 BLC / HLC / WDR(120dB)
 >52dB
 Triple
 1 BNC, impedance 75 Ω; amplitude 1 V [p-p]
 2592 x 1944
 Main Stream: 5MP (2592x1944), Max 20fps; 5MP (2592x1944), Max 25fps (WDR OFF); 4MP (2560x1440), Max 30fps; 3MP (2048x1536), Max 30fps; 2MP (1920x1080), Max 30fps;
 Sub Stream: 2MP (1920x1080), Max 30fps; Third Stream: D1 (720x576), Max 30fps
 Up to 4 areas
 Up to 8 areas
 IR-cut filter with auto switch (ICR)
 Up to 8 areas
 impedance 35 kΩ; amplitude 2 V [p-p]
 impedance 600 Ω; amplitude 2 V [p-p]
 G.711
 Two way Supported
 1 Ch.
 1 Ch.
 IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, ONVIF (Profile S, Profile G, Profile T), API
 ANR, NAS(NFS)
 Support

CP- VNC-V51ZR3-VMD**5 MP Full HD WDR Array Vandal Dome Camera - 30Mtr.****Feature**

Ethernet
Smart Phone
OSD
IR
Micro SD
Casing
Operating Temperature
Humidity
Power Source
Power Consumption
Weatherproof Standard
Dimension
Weight

Specification

10M/100M Base-TX Ethernet
Android, ios
Up to 8 OSDs
Array Range of 30 Mtr., Smart IR
Micro SD, up to 256GB
Metal + Plastic
-40°C ~ 60°C (-40°F ~ 140°F)
≤ 95% RH (non-condensing)
12 V DC±25%, PoE (IEEE802.3 af)
Max.8.7W
IP67 & IK10
Φ148 x 111.3 mm (Ø5.8" x 4.4")
0.92 kg